


PYROSPOT DGE 10N/DGE 10NV

Pyrometers for industry and research

Technical data		
Type	DGE 10N/DGE 10NV	DGE 10N/DGE 10NV
Temperature range	100 °C to 850 °C	150 °C to 1200 °C
Sub temperature range of analog output	adjustable within temperature range, minimum span 50 °C	
Spectral range	2.0 µm to 2.6 µm	
Optics	vario optics with quartz glass protection window, measuring fields from 1.2 mm	
Distance ratio	approx. 100 : 1	approx. 200 : 1
Measurement uncertainty ¹	0.5 % of measured value in °C + 2 K	
Reproducibility ¹	0.3 % of measured value in °C + 1 K	
Transmittance	50 % to 100 %	
Ambient radiation	adjustable within temperature range	
NETD ^{1,2}	0.5 K	
Response time (t ₉₅)	2 ms ³ , adjustable up to 100 s	
Emissivity	0.050 to 1.000, adjustable at the device or via interface	
Storage	minimum and maximum value storage, adjustable via interface	
Output	0/4 to 20 mA, switchable via software, temperature linear, max. burden 500 Ω (galvanically isolated)	
Interface	RS-485 (galvanically isolated), half duplex, baudrate up to 115 kBd, data protocol Modbus RTU	
Switching output/threshold	1 Opto relay, R _{Load} min. 48 Ω/adjustable within temperature range	
Aiming	LED aiming light, laser aiming light (630 to 680 nm, class II, < 1 mW), through-lens sighting or camera module (DGE 10NV)	
Software	PYROSOFT Spot for Windows®, optional: PYROSOFT Spot Pro	
Parameters ⁴	emissivity, transmittance, ambient radiation, response time, temperature unit °C or °F, storage settings, sub temperature range of measurement output, switching thresholds of switching output, key lock	
User controls	Keys for „Parameter Menu“, „Enter“, „Up“ and „Down“, aiming light push-button, display	
Power supply	24 V DC ± 25 %	
Power consumption	max. 1.5 W	
Operating temperature	0 °C to 45 °C	
Storage temperature	-20 °C to 70 °C	
Weight	appr. 520 g	
Dimensions	54 × 54 mm, length 170 mm	
Housing	compact housing with plug connector, display, push-buttons and optics protection window	
Safety class	IP 65 (DIN 40 050)	
CE symbol	according to EU regulations (EN 50 011)	
Scope of delivery	PYROSPOT DGE 10N/DGE 10NV, mounting screw nut, inspection sheet, manual, PYROSOFT Spot for Windows® (without connection cable, please order separately)	

¹T_{ambient} = 23 °C, ε = 1, t₉₅ = 1 s. ²Noise equivalent temperature difference. ³With dynamic adaption at low signal level. ⁴Adjustable via software and interface or directly at the device.

Dimensional drawing pyrometer (with through-lens sighting)




PYROSPOT DGE 10N/DGE 10NV

Pyrometers for industry and research

Vario optics

Measuring distance a [mm]	250	300	350	500	800	4000	Aperture diameter \varnothing D [mm]	Order number		
Optics pullout [mm]	29.2	25.5	23.5	20.3	18.0	15.0	at	LED aiming light	Laser aiming light	
Device	Measuring field diameter M [mm]						a = 250 mm	a = 4000 mm	Through-lens sighting	Camera module
100 °C to 850 °C	2.5	3.0	3.5	5.0	8.0	40.0	8.0	6.5	5101002222	5101012222
									5101022222	5101032222
150 °C to 1200 °C	1.2	1.5	1.7	2.5	4.0	20.0	8.0	6.5	5101002223	5101012223
									5101022223	5101032223

Dimensional drawing vario optics




Technical data video camera (DGE 10NV)

Video signal	Composite video signal approx. 1V _{ss} at 75 Ω (galvanically isolated, video signal can be deactivated via software)
Video norm	PAL (B), 50 Hz (optional video norm NTSC (M), 60 Hz)
Resolution	1/3 inch video chip 628 \times 586 pixels (NTSC option: 510 \times 496 pixels)
Exposure control	Automatic or manual via software or device
Visible field	approx. 8 % \times 6 % of adjusted measurement distance (NTSC option: 6.5 % \times 5 %)
Date/Time	Real-time clock with minimum 3 days power reserve, adjustable via software
Durable image displays	Target mark in measurement spot size; spectral pyrometers: measurement temperature, emissivity
Optional displays	Via software: serial number, device name or user-defined text (16 characters), date, time, temperature unit °C/°F, 12/24 hours display
White balance	Automatic or manual via software or device


Detailed view: Display

The digital display shows the current measured value and the emissivity set as well as further information.



Detailed view: Rear side

The parameters can be adjusted with the keys at the rear side of the device. The set value is taken over directly.



PYROSPOT DGE 10N/DGE 10NV

Pyrometers for industry and research

Electrical, mechanical and optical accessories (more accessories on request)		Part number	
Connection cable, 12 pin, angled plug	Length 2 m	3310A11131	
	Length 5 m	3310A11132	
	Length 10 m	3310A11133	
	Length 15 m	3310A11134	
	Length 20 m	3310A11135	
	Length 25 m	3310A11136	
	Length 30 m	3310A11137	
Video connection cable	Length 2 m	3310A16521	
	Length 5 m	3310A16522	
	Length 10 m	3310A16523	
	Length 15 m	3310A16524	
	Length 20 m	3310A16525	
	Length 25 m	3310A16526	
	Length 30 m	3310A16527	
Interface adapter	RS-485 to USB	3310A14020	
Power supply PSU 15	24 V DC, 0.6 A	3310A12010	
Mounting angle	Adjustable	3310A21020	
Air purge unit	Stainless steel, purge air 0.1 to 0.5 bar, oil-free	3310A22020	
Window slide	without window	3310A21210	
Vacuum flange	KF 16	3310A24015	
	with quartz glass	3310A34021	
	with sapphire glass (scratch-proof)	3310A34051	
Cooling jacket	including air purge unit	3310A23031	
Mounting angle	for cooling jacket	3310A23036	
ATEX housing		3310A23100	
Handheld programming device DHP 1040	mobile device for pyrometer parameterization	3310A17010	
TFT display	TFT display industrial	3.5" with 2 m cable	3310A16110 3310A16120
Adapter	Video/USB	3310A14030	

Selected accessories – images

Mounting angle, adjustable

Part number: 3310A21020



Ball and socket mounting

Part number: 3310A21025



Cooling jacket

Part number: 3310A23031



Cooling plate

Part number: 3310A23020



Air purge unit

Part number: 3310A22020



ATEX housing

Part number: 3310A23100



Technische Änderungen vorbehalten. Technical details are subject to change. 28.11.18



Phone: +49 351 896 74-0
 Fax: +49 351 896 74-99
 Email: info@dias-infrared.de
 Internet: www.dias-infrared.com

DIAS Infrared GmbH
 Pforzheimer Straße 21
 01189 Dresden
 Germany